



## SOVEREIGN CHEMICAL COMPANY

1225 West Market St., Akron OH 44313

Phone: 330-869-0500, Fax: 330-869-0518

www.sovchem.net

# Tartac 30 Liquid

**Manufacturer:** Mobile Rosin Oil Company

**Classification:** Pine tar plasticizer, tackifier and process aid

**Chemical Composition:** Pine Tar

### **Physical Data**

<b>Specification Property</b>	<b>Value</b>
Acid number	50 - 60
Viscosity, Stormer	100-200 secs. 30°C/400 gm. wt.
Moisture	0.5% Maximum
Specific Gravity	0.990 Typical

<b>Typical Property</b>	<b>Value</b>
Appearance	Dark, viscous liquid

**Applications:** Medium viscosity pine tar. Used as a plasticizer, tackifier, and process aid. Can also be used as a replacement for oil when economics or supply warrants. Due to the high acidity, pine tar will retard the cure; this can be offset by adding 3/4 phr of CaO.

### **Packaging and Storage**

**Packaging:** 55 gal. (450 lb net) drums.

**Shelf Life:** 4+ years from date of manufacture if stored as indicated below.

**Storage:** Store in original packaging in a cool dry place. Storing materials above 250°F will cause gradual decarboxylation of the product.

Specification Date: February 25, 2011 (Supersedes: September 2, 1994).