

Sunsine HS OT-20 Oiled Powder

Manufacturer: Shandong Sunsine Chemical Co., Ltd.

Classification: Sulfur

CA Nomenclature: Polymeric Sulfur

Specification Properties	Value	Test Method
Acidity, %	0.05 maximum	ASTM D4569
Ash Content, %	0.1 maximum	ASTM D4574-02
Heat Loss, %	0.5 maximum	ASTM D4571-02
High Temperature Stability @ 105°C	75 minimum	Supplier
Insoluble Sulfur Content, % on total S	90 minimum	ASTM D4578-89
Oil Content, %	19-21	ASTM D4573-02
Sieve Residue on 100 mesh, %	0.3 maximum	ASTM D4572
Total Sulfur Content, %	79-81	ASTM D4574
Typical Properties	Value	Test Method
Physical Form	Yellow powder	Visual
Specific Gravity	1.57	Typical

> APPLICATIONS

Uses: Non-staining, non-coloring Sulfur curing agent. Used to retard bin scorch, prevent migration of sulfur and preserve surface tack which is important in the manufacture of tires and other plied-up rubber goods.

> PACKAGING AND STORAGE

Packaging: 25 kg (55.1 lb.) bags

Shelf Life: 2 years from date of manufacture if stored as indicated below.

Storage: Store in a well-ventilated area below 30°C, avoiding direct sunlight. Do not store near products that can emit free amines such as sulfenamides and DTDM. Amines and other alkaline vapors cause Sunsine HD-OT20 to revert to Rubber Maker Sulfur at any temperature. High temperatures also cause reversion to Rubber Maker Sulfur.

Specification Date: July 14, 2016 (Supersedes June 8, 2012)